

Paper Carrier Ropes

	Predryer	Dryer	Postdryer	Pope Reel	Sizepress	Coater	Creping Unit	High speed machines	Paper grammage over 140 g/m ²	Temperature	Extra grip
Powerline UNO	✓	✓	✓	✓						up to 180 °C / 356 °F	
Powerline DUO	✓	✓	✓	✓				✓	✓	up to 180 °C / 356 °F	
Superline UNO	✓	✓	✓	✓	✓	✓	✓			up to 180 °C / 356 °F	
Superline DUO	✓	✓	✓	✓	✓	✓	✓	✓	✓	up to 180 °C / 356 °F	
Safegrip UNO	✓	✓	✓		✓	✓				up to 180 °C / 356 °F	Good
Gripline UNO	✓	✓	✓		✓	✓				up to 180 °C / 356 °F	Very good
Doubleline UNO	✓	✓	✓		✓	✓				up to 180 °C / 356 °F	
Doubleline DUO	✓	✓	✓	✓	✓	✓	✓	✓	✓	up to 180 °C / 356 °F	
Compact UNO					✓	✓	✓			up to 180 °C / 356 °F	
Compact R					✓	✓	✓	✓	✓	up to 180 °C / 356 °F	
Extraline UNO					✓	✓				up to 180 °C / 356 °F	Excellent
Extraline DUO					✓	✓		✓	✓	up to 180 °C / 356 °F	Excellent
Technoline UNO	✓	✓	✓		✓	✓				up to 180 °C / 356 °F	
Technoline DUO	✓	✓	✓	✓	✓	✓	✓	✓	✓	up to 180 °C / 356 °F	
UHT UNO	✓	✓	✓		✓	✓				up to 300 °C / 572 °F	
UHT R	✓	✓	✓		✓	✓				up to 300 °C / 572 °F	



optimal solution

UNO hollow rope without core

DUO rope with core, best solution for high speed machine and high grammage of paper

R hollow rope without core, extra round shape, alternative to ropes with core

Available colours: red, blue, green, yellow, white, purple

Diameter range: 8.5 – 16 mm, 21/64 – 5/8 inch